

SIMPLEX CONTROL PANELS

3 PH, 200 V

for Sewage, Effluent &
Non-Clog Pumps



Enclosure	Type 4X Polycarbon
Circuit breaker	For pump and control circuit
Motor starter	IEC rated with class 10 overload
HOA switch	Three position toggle HP rated
Alarm switch	Three position toggle HP rated
Run light	Amber neon pilot light
Transformer	With fuse protection
Moisture sensor*	Seal fail circuit and light
Temp sensor*	Heat sensor connections
Bracket	Bright aluminum
Fuse	Control and alarm sized at 3 amps
Terminal strip	Box type lugs sectional
Wiring	Color coded
Visible alarm	360 degree flashing
Audible alarm	Piezo buzzer
Level control	Requires 3 floats rated at 2 amps
Certifications	UL 508A

* Requires sensor to be in pump.

Consult factory for other available options. Some options may require an increase in the enclosure size.



V	PH	Amps	Part number
200	3	2.4 - 4	BPH03S4XNM004
200	3	4 - 6	BPH03S4XNM006
200	3	6 - 10	BPH03S4XNM010
200	3	9 - 12	BPH03S4XNM012
200	3	10 - 16	BPH03S4XNM016
200	3	16 - 18	BPH03S4XNM018
200	3	18 - 24	BPH03S4XNM024
200	3	24 - 32	BPH03S4XNM032
200	3	32 - 40	BPH03S4XNM040

NOTE: Overloads must be located in pump.

