

 INDUSTRIAL FLOW SOLUTIONS™	TECHNICAL DATA			BJM Pumps® KB55		
	Dwg:	DS-C10-013	Rev:	1	Date:	8/15/2025

GENERAL DATA

MAX. FLOW:	445 GPM (1684.5 L/min)
MAX. HEAD:	86' (26.2m)
MAX. SUBMERSION DEPTH:	65' (20m) or limited to length of power cord, Consult factory for deeper depths
PUMP TYPE	DEWATERING/LIGHT SLURRY TOP DISCHARGE
MINIMUM SUBMERSION DEPTH: FOR CONT. DUTY ³	28.5" (724 mm)
PUMP DOWN WATER LEVEL:	7.52" (191 mm)
SOLID SIZE:	0.4" (10 mm)
IMPELLER DIAMETER:	5.5" (139 mm)
DISCHARGE SIZE	4" NPT-MALE
PUMP WEIGHT (without cable):	254 lbs (115 kg)
SHIPPING WEIGHT:	335 lbs (152 kg)

CONSTRUCTION / MATERIAL DATA

UPPER MECHANICAL SEAL	CARBON/CERAMIC, FKM
LOWER MECHANICAL SEAL	SILICON CARBIDE/ SILICONE CARBIDE, FKM
MOTOR HOUSING	CAST IRON
PUMP VOLUTE	DUCTILE IRON
WEAR PLATE	HI-CHROME
AGITATOR	HI-CHROME
IMPELLER	HI-CHROME
STAND	STEEL
LIP SEAL & O-RINGS	BUNA-N
ROTOR SHAFT	304 SS
EXTERNAL HARDWARE	304 SS
BALL BEARING: PERM. LUBE. UPPER	6306
BALL BEARING: PERM. LUBE. LOWER	6308

ELECTRICAL / MOTOR DATA

MOTOR: HP, TYPE, RATING	7.5, SUBMERSIBLE , (CONTINUOUS DUTY ³)		
MOTOR RPM	3450		
MOTOR INSULATION CLASS	H		
MOTOR SERVICE FACTOR	1.1		
VOLTAGE - 60Hz ¹	230V	460V	575V
CURRENT F.L.A.	20.4	9.9	7.6
LOCKED ROTOR CURRENT (LRA)	126	63	50
POWER CABLE: GAGE-LENGTH	AWG 10/5, 50' (15m) SOOW		
SENSOR CABLE: (OPTIONAL ²) GAGE-LENGTH	AWG 18/2, 50' (15m) SOOW		
MOTOR PROTECTION	THERMAL & AMP. OVERLOAD		
SEAL LEAK DETECTOR (OPTIONAL ²)	Seal Minder® MOISTURE SENSING PROBE		
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)		

1 - Available in other voltages for 50Hz

2 - Requires a seal fail circuit in control panel for warning signal

3 - Continuous duty motor - see minimum submersion depth above

©2025 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA

(860) 631-3618 • www.flowsolutions.com

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



INDUSTRIAL
FLOW
SOLUTIONS™

PERFORMANCE CURVE

BJM Pumps® KB55

Dwg:




DS-C10-009

Rev:

1

Date:

6/20/2025



Flow

Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C

55 - Dual Units

Frequency
Pump Speed
Impeller

60 Hz
3450 RPM
139mm

Specifications subject to change without notice